

Twintex®

Cintas tubulares com capa adicional de segurança

Nome do item curto	Carga Limite de Trabalho (WLL) [kg]	Carga Limite de Trabalho (WLL) [t]	L1 [m]	L1 min. [m]	Espessura sob carga [mm]	Peso Net [kg]	Peso do metro adicional [kg/m]
Twintex 1t 1m	1000	1	1	0.38	4	0.3	0.3
Twintex 1t 2m	1000	1	2	0.38	4	0.6	0.3
Twintex 1t 3m	1000	1	3	0.38	4	0.9	0.3
Twintex 1t 4m	1000	1	4	0.38	4	1.2	0.3
Twintex 1t 5m	1000	1	5	0.38	4	1.5	0.3
Twintex 2t 1m	2000	2	1	0.38	6	0.5	0.5
Twintex 2t 2m	2000	2	2	0.38	6	1	0.5
Twintex 2t 3m	2000	2	3	0.38	6	1.5	0.5
Twintex 2t 4m	2000	2	4	0.38	6	2	0.5
Twintex 2t 5m	2000	2	5	0.38	6	2.5	0.5
Twintex 3t 1m	3000	3	1	0.38	7	0.6	0.6
Twintex 3t 2m	3000	3	2	0.38	7	1.2	0.6
Twintex 3t 3m	3000	3	3	0.38	7	1.8	0.6
Twintex 3t 4m	3000	3	4	0.38	7	2.4	0.6
Twintex 3t 5m	3000	3	5	0.38	7	3	0.6
Twintex 4t 1m	4000	4	1	0.5	8	0.8	0.8
Twintex 4t 2m	4000	4	2	0.5	8	1.6	0.8
Twintex 4t 3m	4000	4	3	0.5	8	2.4	0.8
Twintex 4t 4m	4000	4	4	0.5	8	3.2	0.8



Nome do item curto	Carga Limite de Trabalho (WLL) [kg]	Carga Limite de Trabalho (WLL) [t]	L1 [m]	L1 min. [m]	Espessura sob carga [mm]	Peso Net [kg]	Peso do metro adicional [kg/m]
Twintex 4t 5m	4000	4	5	0.5	8	4	0.8
Twintex 5t 1m	5000	5	1	0.5	9	1	1
Twintex 5t 2m	5000	5	2	0.5	9	2	1
Twintex 5t 3m	5000	5	3	0.5	9	3	1
Twintex 5t 4m	5000	5	4	0.5	9	4	1
Twintex 5t 5m	5000	5	5	0.5	9	5	1
Twintex 6t 1m	6000	6	1	0.75	12	1.3	1.3
Twintex 6t 2m	6000	6	2	0.75	12	2.6	1.3
Twintex 6t 3m	6000	6	3	0.75	12	3.9	1.3
Twintex 6t 4m	6000	6	4	0.75	12	5.2	1.3
Twintex 6t 5m	6000	6	5	0.75	12	6.5	1.3
Twintex 8t 1m	8000	8	1	0.75	13	1.8	1.8
Twintex 8t 2m	8000	8	2	0.75	13	3.6	1.8
Twintex 8t 3m	8000	8	3	0.75	13	5.4	1.8
Twintex 8t 4m	8000	8	4	0.75	13	7.2	1.8
Twintex 8t 5m	8000	8	5	0.75	13	9	1.8

Nome do item curto	Cor
Twintex 1t 1m	Roxo
Twintex 1t 2m	Roxo
Twintex 1t 3m	Roxo



Nome do item curto	Cor
Twintex 1t 4m	Roxo
Twintex 1t 5m	Roxo
Twintex 2t 1m	Verde
Twintex 2t 2m	Verde
Twintex 2t 3m	Verde
Twintex 2t 4m	Verde
Twintex 2t 5m	Verde
Twintex 3t 1m	Amarelo
Twintex 3t 2m	Amarelo
Twintex 3t 3m	Amarelo
Twintex 3t 4m	Amarelo
Twintex 3t 5m	Amarelo
Twintex 4t 1m	Cinza
Twintex 4t 2m	Cinza
Twintex 4t 3m	Cinza
Twintex 4t 4m	Cinza
Twintex 4t 5m	Cinza
Twintex 5t 1m	Vermelho
Twintex 5t 2m	Vermelho
Twintex 5t 3m	Vermelho
Twintex 5t 4m	Vermelho
Twintex 5t 5m	Vermelho
Twintex 6t 1m	Marrom
Twintex 6t 2m	Marrom
Twintex 6t 3m	Marrom
Twintex 6t 4m	Marrom
Twintex 6t 5m	Marrom



Nome do item curto

Cor

Twintex 8t 1m

Blue

Twintex 8t 2m

Blue

Twintex 8t 3m

Blue

Twintex 8t 4m

Blue

Twintex 8t 5m

Blue

REFERÊNCIA PARA PEDIDO[Global Item Number/Local ERP Number SSBR]

Dimensão L1	1000 kg	2000 kg	3000 kg	4000 kg	5000 kg	6000 kg	8000 kg
1 m	2003714	2003716	2003718	2003720	2003722	2003724	2003726
2 m	2003218	2003220	2003222	2003224	2003226	2003228	2003230
3 m	2003217	2003219	2003221	2003223	2003225	2003227	2003229
4 m	2002730	2002732	2002734	2002736	2002738	2002740	2002742
5 m	2002729	2002731	2002733	2002735	2002737	2002739	2002741

■ Normas	EN 1492-2: 2000
■ Material principal	Poliéster
■ Gama de temperaturas	- 40°C / 100°C
■ Proteção da etiqueta	Não
■ Unidade de embalagem (PU) Conteúdo	1

1. WLL - working load limit, nominal load capacity. Applies to direct attachment type.
2. L1 - working length.
3. Deviating from DIN EN 1492-2, the material in this round sling is suitable up to an operating temperature of +70°C.
4. In DIN EN 1492-2, HMPE is not listed as a material and material mixtures are not provided for.

