

TWINTEX Eye and Eye

Lifting sling with extra abrasion protection, Built to outlast, Reliable Lifting Power with Reinforced Eyes for Extra Durability

Item Name short	WLL Vertical [lbs]	WLL Choker [lbs]	WLL 90° Basket lbs [lbs]	Weight per Foot [lbs/ft]	Minimum Length [ft.]	Standard Eye Length [in]	Approx. Width At Load [in]
EY30 CL	2600	2100	5200	0.3	3	10	1.7
EY60 CL	5300	4200	10600	0.4	3	10	2.2
EY90 CL	8400	6700	16800	0.6	3	12	2.5
EY120 CL	10600	8500	21200	0.7	3	12	2.5
EY150 CL	13200	10600	26400	0.8	4	14	3.2
EY180 CL	16800	13400	33600	1	4	16	3.3
EY240 CL	21200	17000	42400	1	4	16	3.7

Item Name short	Color
EY30 CL	Purple
EY60 CL	Green
EY90 CL	Yellow
EY120 CL	Tan
EY150 CL	Red
EY180 CL	White
EY240 CL	Blue

ORDER NUMBERS[Global Item Number/Local ERP Number SSUS]

2600 lbs	5300 lbs	8400 lbs	10600 lbs	13200 lbs	16800 lbs	21200 lbs
2012754 EY30 CL	-	-	-	-	-	-
-	2012755 EY60 CL	2012756 EY90 CL	2012757 EY120 CL	2012758 EY150 CL	2012759 EY180 CL	2012760 EY240 CL

- Temperature Range -40°C bis +100°C
- Packaging Unit (PU) Content 1

SpanSet, Inc.
3125 Industrial Drive
Sanford, NC 27331
United States of America
800-334-7505
info@spanset.com
www.spanset.com



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet, Inc. - USA

**SpanSet
Certified
Safety**