




TWN 1820 XL-LOK verbindingsschalm

Gebruikt om hijskettingen met aanslagcomponenten te verbinden voor het samenstellen van kettingsamenstellingen en sjorringen

Item Naam kort	WLL [kg]	Kettingdiameter	WLL [t]	A [mm]	B [mm]	C [mm]	E [mm]
F30807	1400	6 mm	1.40	61	12	38.5	45
F308090	1900	7 mm	1.90	71	14	47	50.5
F30817	2500	8 mm	2.50	85	16	55	62
F30827	4000	10 mm	4	97	18	66.5	72
F30837	6700	13 mm	6.70	125	23	82.5	87
F30847	10000	16 mm	10	146	31.5	109	105
F308570	16000	20 mm	16	178.5	37	143.5	127.5
F308670	19000	22 mm	19	196.5	40.5	150.5	140.5
F308770	26500	26 mm	26.50	232	47.5	178	166
F308870	40000	32 mm	40	285.5	58.5	220.5	204

Item Naam kort	F [mm]	G [mm]	Lopende meter [kg]
F30807	8	14	0.07
F308090	9	16	0.14
F30817	10	19	0.20
F30827	13	24	0.35
F30837	17	28	0.74
F30847	21	34	1.20
F308570	25	45	2.80
F308670	27.5	45	3.50
F308770	33	56	5.80
F308870	40	70	10.90



BESTELNUMMERS[Global Item Number/Local ERP Number SSNL]

Kettingdiameter	F30807	F30817	F30827	F30837	F30847	F308090	F308570	F308670	F308770	F308870
6 mm	2032539	-	-	-	-	-	-	-	-	-
8 mm	-	2032541	-	-	-	-	-	-	-	-
10 mm	-	-	2032546	-	-	-	-	-	-	-
13 mm	-	-	-	2032547	-	-	-	-	-	-
16 mm	-	-	-	-	2032548	-	-	-	-	-
7 mm	-	-	-	-	-	2032540	-	-	-	-
20 mm	-	-	-	-	-	-	2032549	-	-	-
22 mm	-	-	-	-	-	-	-	2032550	-	-
26 mm	-	-	-	-	-	-	-	-	2032551	-
32 mm	-	-	-	-	-	-	-	-	-	2032552

- Graden 100
- Hoofdmateriaal Staal
- Kleur Blauw
- Verpakkingseenheid (PU) Inhoud 1

