

VarioForce 2-Strang

Präzise und schnell asymmetrische Lasten heben!

Artikel Name kurz	Öse	Haken- Komponente	WLL t Winkel 0°- 45° [t]	WLL t Winkel 45°- 60° [t]	L1 min. [m]	Gewicht für 1m [kg]	Nettogewicht kg [kg]
VF2-1000- ESHC	MLF-108-10	ESHC-6-10	1.4	1	1.5	2	3
VF2-1000- ESLH	MLF-108-10	ESLH-6-10	1.4	1	1.5	2	3
VF2-2000- ESHC	MLF-108-10	ESHC-8-10	2.8	2	1.5	3.6	5.5
VF2-2000- ESLH	MLF-108-10	ESLH-8-10	2.8	2	1.5	3.6	5.5
VF2-3000- ESHC	MLF-1310-10	ESHC-10-10	4.2	3	2.5	4.25	10.6
VF2-3000- ESLH	MLF-1310-10	ESLH-10-10	4.2	3	2.5	4.3	10.6

Artikel Name kurz	Gewicht pro Meter [kg/m]
VF2-1000-ESHC	0.6
VF2-1000-ESLH	0.6
VF2-2000-ESHC	0.9
VF2-2000-ESLH	0.9
VF2-3000-ESHC	1.2
VF2-3000-ESLH	1.2



BESTELLNUMMERN[Global Item Number/Local ERP Number SSCH]

Haken-Komponente	1.4 t	2.8 t	4.2 t
 ESHC-6-10	2032308 VF2-1000-ESHC	-	-
 ESLH-6-10	2032311 VF2-1000-ESLH	-	-
 ESHC-8-10	-	2032309 VF2-2000-ESHC	-
 ESLH-8-10	-	2032312 VF2-2000-ESLH	-
 ESHC-10-10	-	-	2032310 VF2-3000-ESHC
 ESLH-10-10	-	-	2032313 VF2-3000-ESLH

■ Normen	based on EN 1492-2
■ Hauptmaterial	Hochleistungsfasern polyethylen (HMPE)
■ Farbe	Schwarz
■ Temperaturbereich	-40°C / +100°C
■ Verpackungseinheit (VPE) Inhalt	1

