

VarioWeb regolabile 4-bracci

Sollevamento di carichi asimmetrici

Nome articolo breve	Connesso alla catena	WLL kg [kg]	L1 [m]	L1 min. [m]
VW4 2100 4EH 4m/5m	-	2100	-	-
VW4-2100-4ASH	-	2100	-	2000
VW4-2100-2ASH	-	2100	-	2000
-	-	2100	2	-
VW4 2100 4Joker 2m	No	2100	2	-
VW4 2100 4EH 2m	-	2100	2	-
VW4 4200 2Joker 2m	No	2100	2	-
VW4 2100 2Joker 2m	No	2100	2	-
VW4 2100 4Joker 3m	-	2100	3	-
VW4 4200 2Joker 3m	No	2100	3	-
VW4 2100 2Joker 3m	No	2100	3	-
VW4 2100 4EH 3m	No	2100	3	-
VW4 2100 4Joker 4m	No	2100	4	-
VW4 2100 4EH 4m	No	2100	4	-
VW4 4200 2Joker 4m	No	2100	4	-
VW4 2100 2Joker 4m	No	2100	4	-
VW4 4200 2EH 2m	-	4200	2	-
VW4 4200 2Joker 2m	-	4200	2	-
VW4 4200 4Joker 2m	-	4200	2	-
VW4 4200 4EH 2m	-	4200	2	-
VW4 4200 2EH 3m	-	4200	3	-
VW4 4200 4Joker 3m	-	4200	3	-
VW4 4200 4EH 3m	-	4200	3	-
VW4 4200 2Joker 3m	-	4200	3	-
VW4 4200 4Joker 4m	-	4200	4	-
VW4 4200 2EH 4m	-	4200	4	-
VW4 4200 4EH 4m	-	4200	4	-
VW4 4200 2Joker 4m	-	4200	4	-



ARTICOLO[Global Item Number/Local ERP Number SSIT]

WLL kg	Dimensione L1	4
2100 kg	-	2019240,2004336,2003831
2100 kg	2 m	2012481,2004337,2004333,2002921,2003832
2100 kg	3 m	2004338,2003383,2003833,2004334
2100 kg	4 m	2004339,2004335,2003830,2003834
4200 kg	2 m	2012405,2012424,2012453,2012483
4200 kg	3 m	2012448,2012454,2012486,2012549
4200 kg	4 m	2012452,2012464,2012485,2012487

- **Norme** EN 1492-1
- **Intervallo di temperatura** -40°C / +100°C
- **Packaging Unit (PU) Contenuto** 1

