


Zurrurt Typ ABS50 mit ABS-Ratsche und Drahhaken

Zweiteiliger 50 mm-Zurrurt, mit ABS-Ratsche, LC 2'500 / 5'000 daN



Artikel Name kurz	L1 [m]	L3 [m]	Nettogewicht kg [kg]
ABS LS LC2500 50mm double wire 6m	6	5.6	3.96
ABS LS LC2500 50mm double wire 8m	8	7.6	4.26
ABS LS LC2500 50mm double wire 10m	10	9.6	4.54

BESTELNUMMERN[Global Item Number/Local ERP Number SSCH]

Länge L1	ABS LS LC2500 50mm double wire 6m	ABS LS LC2500 50mm double wire 8m	ABS LS LC2500 50mm double wire 10m
6 m	2010059 ABS50629	-	-
8 m	-	2010060 ABS50829	-
10 m	-	-	2010061 ABS501029

■ Normen	EN 12195-2
■ Verbindungselement (VE)	DJH-50 SSCH
■ Oberflächenbeschichtung	Verzinkt
■ Gurtband Material	Polyester, thermofixiert und dehnungsarm <4%
■ Hauptmaterial	Polyester
■ Farbe	Gelb
■ Gurtband Breite B	50 mm
■ Zurrkraft LC	2'500 daN
■ Vorspannkraft STF	350 daN
■ Vorspannkraft STF (mit TFI)	500 daN
■ Temperaturbereich	-40° C to + 100° C
■ Vorspannindikator (TFI)	Ja
■ Etikettenschutz	Ja
■ Verpackungseinheit (VPE) Inhalt	1

