Inspection points for webbing slings and roundslings

Visual check of lifting slings that can be repaired: Can be used after successful repair!


Label missing or no longer legible, but the manufacturer is known


The webbing cross-section is damaged by less than 10 %


Only the sling **eye** reinforcement is damaged

Note:
Lifting slings that can be repaired may only be re-used after their proper repair by the manufacturer or an authorised agent. Under no circumstances may they continue to be used unrepaired or repaired by third parties.

Visual check: Remove from service and destroy webslings


Manufacturer unknown


Damage to more than 10 % of the cross-section


Main seam damaged

Note:
Lifting slings that are to be discarded, i.e. are irreparable, must be safely withdrawn from use! But don't take any risks! These lifting slings may not be used even with a reduced lifting capacity!


Damage to the slings (not the reinforcement)



Damaged by heat


Damaged by acids/**alkalis**

Visual check of roundslings that can be repaired: Can be used following approved repair and re-certification


Label missing or no longer legible, but the manufacturer is known


Only the sleeve or stitching is defective (the strands must be undamaged)

Note:
Roundslings that can be repaired may only be re-used after their proper repair by the manufacturer or an authorised agent. Under no circumstances may they continue to be used unrepaired or repaired by third parties.

Visual check: Remove from service and destroy roundslings.


Manufacturer unknown


Damage to the internal strands

Note:
Roundslings that are to be discarded, i.e. are irreparable, must be safely withdrawn from use! But don't take any risks! These round slings may not be used even with a reduced lifting capacity!


Damaged by acids/**alkalis**



Damaged by heat

SpanSet UK Limited
Telford Way, Middlewich
Cheshire CW10 0HX

Tel +44 (0) 1606 737494
Fax +44 (0) 1606 737502

E-Mail: customerservices@spanset.co.uk
www.spanset.co.uk